


Accessories

Accessories for the HTI headboard

- SR-HTI. Mounting bracket for installing the headend in a 19" rack
- USB-300. USB-Ethernet adapter for local or remote control.
- COR-150. Schuko network cable.



SR-HTI



COR-150



USB-300

MODEL	USB-300	
Part number	4284	
Connectivity		
Number of outputs	RJ-45 Ethernet port (10/100/1000 Mbps)	USB Type A connector
LEDs	Speed (orange)	Link/ACT (green)
Standards	USB Specification Version 3.0 USB Specification Version 2.0 USB Specification Version 1.1 USB Specification Version 1.0 OHCI (Open Host Controller Interface)	EHCI (Enhanced Host Controller Interface) IEEE 802.3 Ethernet IEEE 802.3u 100BASE-T, TX, and T4 compatible Supports sleep mode and remote boot Supports full and half duplex in Gigabit Ethernet mode
General		
System Requirements	Operating System: Microsoft Windows 8/7/Vista/XP SP3	Mac OS 10.6 to 10.8 Linux kernel 2.6.14x or higher
Power Management	Advanced power management reduces power consumption when there is little or no traffic	
Physical		
Power	Input: Via USB at 500 mA, 5 V DC	Power consumption: 150 mA, 3.3 V DC
Temperature	In use: 0 to 45 °C (32 to 113 °F)	Storage: -20 to 70 °C (-4 to 158 °F)
Humidity	In use: 10% to 90% non-condensing	Storage: 5% to 90% non-condensing
Dimensions	74.4 x 21 x 16 mm (2.93 x 0.83 x 0.063 inches)	
Weight	46.4 grams (1.64 ounces)	
Certifications	CE	FCC