

OPTICAL FIBRE INSTALLATIONS

FIBER ADAPTERS

Simplex and Duplex SC-SC/APC SM

APPLICATION

- Adapters for SC-SC (female-female) APC fibre optic connectors in simplex and duplex format, green zirconia.
- Use in boxes, panels, trays, rosettes and any fibre optic equipment in telecommunication networks, CATV, LAN, broadband, FTTH, etc.
- They incorporate a black and a translucent cap for easy identification by means of a VFL.



ADF-102



ADF-103



ADF-104

MODEL		ADF-102	ADF-103	ADF-104
Reference		8040		
Connector type		SC-SC	SC-SC	SC-SC
Polishing		APC	APC	APC
Fiber		SM	SM	SM
Format		Simplex With fixing screws	Simplex Without fixing screws	Duplex With fixing screws
Material	Plug	Translucent propylene - PP		
	Flange	Acero inoxidable - SUS304		
	Housing	Polycarbonate - PC		
	Core	Tereftalato de polietileno - PET+GF		
	Ferrula	Ceramic - Zirconia ZrO2		
Tensile strength		2,0 ~ 5,9 N		
Insertion loss		≤ 0,25 dB		
Wavelength		1310nm ~ 1550nm ~ 850nm		
Durability	Cycles	> 500 veces		
	Loss	< 0,2 dB		
Operating temperature		-40 ... +75 °C		

MODEL		TA-001
Reference		8290

Fibreboard adapter fixing screws (Bag of 50 pieces)