

UNIVERSAL OUTPUT MODULE (OUT)

FLOW-OUT

APPLICATION

The FLOW OUT module generates 4 or 6 RF carriers (depending on the selected mode) in DVB-T, DVB-C or J.83 Annex B format.

When OUT4 mode is selected, 4 RF carriers will be generated. Each carrier can convey up to 8 television or radio services (SPTS).

When OUT 6 mode is selected, 6 RF carriers will be generated, each one with 6 television or radio services (SPTS) as maximum.

Each Flow headend may have several OUT modules, whose RF carriers are all combined and amplified by the FLOW BASE.



MODEL		FLOW-OUT
Referencia		4313
IPTV INPUTS		
Interface type		Gigabit Ethernet
Standard		1000Base-T
VLAN support		Sí
RF OUTPUT		
Number of outputs RF carriers		4 in OUT4 mode 6 in OUT6 mode
Number of SPTS per RF carriers		8 in OUT4 mode 6 in OUT6 mode
Total SPTS		32 in OUT4 mode 36 in OUT6 mode
Standards supported		DVB-T EN 300 744 DVB-C EN 300 429 J.83 Anexo B
MER	dB	> 42
GENERAL		
Power supply voltage	Vdc	24
Power consumption	W	21,5
Operating temperature	°C	0 ... 45
Weight	g	425
Dimensions (Height x Width x Depth)	mm	125 x 27 x 210