


ICT installations

User terminal box with 2 ports
+ pigtail with connector on
one end

FEATURES

- Pigtail specially designed for FTTH and ICT2 infrastructure.
- Includes a user terminal box with SC/SC APC connectors and adapters.
- The cable used is type CFA-002D with two tight-spliced fibres and a tensile strength of >450 N.
- Available in various lengths: 10, 15, 20, 25, 30, 40, 55 and 70 metres of cable for outdoor use.



PAUF-100D Series

MODEL	PAUF-110D	PAUF-115D	PAUF-120D	PAUF-125D	PAUF-130D	PAUF-140D	PAUF-155D	PAUF-170D
Reference	8002	8003	8004	8005	8006	8007	8008	8009
Cable length	10 m	15 m	20 m	25 m	30 m	40 metres	55 metres	70 m
Manufacturing material	ABS							
Protection rating	IP44							
Dimensions	115 x 80 x 21 mm							
Material: Plastic	UL 94 V-0 (Flammability safety standard)							
Colour	White (RAL9003)							
Adapters	2 x SC/APC							
Accessories	2 x M3 screw and plug + 2 x fusion protectors							
SC/SC adapters								
Fibre type	SM							
Polish	APC							
Dust protection	Spring-loaded hinged cover							
2-fibre cable, G657A2-LSZH CFA-002D								
Number of fibres	2							
Core and cladding diameter	9 / 125 µm (124.8±0.7)							
Shrink-wrapped fibre jacket								
Diameter	850 µm ±50 µm							
Material	LSZH							
Colour	Green, red							
Outer sheath								
Outer diameter	4 ±0.2 mm							
Thickness	0.8 mm ±0.05 mm							
Material	LSZH-FR							
CPR	Dca-s2, d2, a2							
Colour	Ivory RAL 1015							
Internal protection	Aramids							
SC connectors								
Connector type	SC							
Polished	APC							
Connection type	Polished							
Insertion loss IL	0.2 dB							