


ICT installations

User terminal box with 2 ports
+ pigtail with connector
at both ends

FEATURES

- Connectors protected for installation in 20 mm diameter conduits, with a minimum bend radius of 7 cm.
- Pre-terminated pigtails at both ends for FTTH and ICT infrastructure.
- User terminal box with SC/SC APC connectors and adaptors.
- The cable used is type CFA-002D with two fitted fibres and a tensile strength >450 N. Pull-box packaging.
- Available in various lengths: 10, 15, 20, 25, 30, 40, 55 and 70 metres of cable for outdoor use.



PAUF-200D Series

MODEL	PAUF-210D	PAUF-215D	PAUF-220D	PAUF-225D	PAUF-230D	PAUF-240D	PAUF-255D	PAUF-270D
Reference	8011	8012	8013	8014	8015	8016	8017	8018
Cable length	10 m	15 m	20 m	25 m	30 m	40 metres	55 metres	70 m
Manufacturing material	ABS							
Protection rating	IP44							
Dimensions	115 x 80 x 21 mm							
Material: Plastic	UL 94 V-0 (Flammability safety standard)							
Colour	White (RAL9003)							
Adapters	2 x SC/APC							
Accessories	2 x M3 screw and plug							
SC/SC adapters								
Fibre type	SM							
Polish	APC							
Dust protection	Spring-loaded hinged cover							
2-fibre cable G657A2-LSZH CFA-002D								
Number of fibres	2							
Core and cladding diameter	9 / 125 µm (124.8±0.7)							
Shrink-wrapped fibre jacket								
Diameter	850 µm ±50 µm							
Material	LSZH							
Colour	Green, red							
Outer sheath								
Outer diameter	4 ±0.2 mm							
Thickness	0.8 mm ±0.05 mm							
Material	LSZH-FR							
CPR	Dca-s2, d2, a2							
Colour	Ivory RAL 1015							
Internal protection	Aramids							
SC connectors								
Connector type	SC							
Polished	APC							
Connection type	Polished							
Insertion loss IL	0.2 dB							